

Photo DMOS-FET Relay

Description

The **LU834** is a miniature 1-Form B solid state relay in an 6 pin DIP package that employs optically coupled MOSFET technology to provide 3750V of input to output isolation. The optically coupled input is controlled by a highly efficient GaAlAs infrared LED and MOS FETs on the output side.

Features

- Low driver power requirements (TTL/CMOS Compatible)
- Contact form: Normally-On (1b)
- Load voltage: 60V max.
- On-Resistance: 3Ω max.
- 3750 Vrms Input/Output isolation
- Tape & Reel version available

Applications

- Telecommunications (PC, Electronic notepad)
- Measuring and Testing equipment
- Industrial control
- Security equipments
- High speed inspection machine

Outline Dimensions




Photo DMOS-FET Relay Specifications

Part Name: LU834

(Load voltage: 60V / Load current: 500mA)

Absolute Maximum Ratings (Ambient Temperature: 25°C)

| Item | | Symbol | Value | Units | Note |
|---------------------------|--------------------------|--------|-------------|------------------|------------------|
| Input | Continuous LED Current | IF | 50 | mA | |
| | Peak LED Current | IFP | 500 | mA | f=100Hz, duty=1% |
| | LED Reverse Voltage | VR | 5 | V | |
| | Input Power Dissipation | PIn | 75 | mW | |
| Output | Load Voltage | VL | 60 | V(AC peak or DC) | |
| | Load Current | IL | 500 | mA | |
| | Peak Load Current | IPeak | 0.6 | A | 1ms(1 pulse) |
| | Output Power Dissipation | Pout | 300 | mW | |
| Total Power Dissipation | | PT | 350 | mW | |
| I/O Breakdown Voltage | | VI/O | 3750 | Vrms | RH=60%, 1min |
| Operating Temperature | | Topr | -40 to +85 | °C | |
| Storage Temperature | | Tstg | -40 to +100 | °C | |
| Pin Soldering Temperature | | Tsol | 260 | °C | 10 sec max. |

Electrical Specifications (Ambient Temperature: 25°C)

| Item | | Symbol | MIN. | TYP. | MAX. | Units | Conditions |
|--------------|---------------------------|--------|------------------|------|------|-------|--|
| Input | LED Forward Voltage | VF | | 1.2 | 1.4 | V | IF=10mA |
| | Operation LED Current | IFon | | 0.5 | 3.0 | mA | |
| | Recovery LED Current | IFoff | 0.1 | 0.4 | | mA | |
| | Recovery LED Voltage | VFoff | 0.5 | | | V | |
| Output | On-Resistance | Ron | | 1 | 3 | Ω | IF=0mA, IL=50mA, Time to flow is within 1 sec. |
| | Off-State Leakage Current | ILeak | | | 1 | uA | IF=5mA, VL=60V |
| | Output Capacitance | Cout | | 165 | | pF | IF=5mA, VL=0, f=1MHz |
| Transmission | Turn-On Time | Ton | | 0.2 | 1.0 | ms | IF=5mA, IL=50mA |
| | Turn-Off Time | Toff | | 0.5 | 3.0 | ms | |
| Coupled | I/O Isolation Resistance | Ri/o | 10 ¹⁰ | | | Ω | DC500V |
| | I/O Capacitance | Ci/o | | 0.8 | | pF | f=1MHz |



Reference Data

