



SH12864D (128 DOTS X 64 DOTS)

FEATURES

- ◆ BUILT-IN CONTROLLER (NT7532 OR EQUIVALENT)
- ◆ +3.3 V POWER SUPPLY
- ◆ 1/64 DUTY CYCLE
- ◆ 8-BIT PARALLEL INTERFACE

MECHANICAL DATA

ITEM	DIMENSIONS	UNIT
Module Size (W x H x T)	40.3 x 35.0 x 4.5	mm
Viewing Area (W x H)	33.8 x 22.2	mm
Active Area (W x H)	30.705 x 19.185	mm
Dot Size (W x H)	0.225 x 0.285	mm
Dot Pitch (W x H)	0.24 x 0.30	mm

INTERFACE PIN CONNECTIONS

NO.	SYMBOL	LEVEL	FUNCTION
1	Vss	0V	Power Supply Ground
2	VDD	3.0V	Power Supply Voltage
3	NC	-	No Connection
4	/RES	H/L	Reset Signal
5	/CS	L	Chip Signal
6	A0	H/L	Data / Command Select
7	/WR	L	Write Signal
8	/RD	L	Read Signal
9~16	DB0~DB7	H/L	Data Bus Line
17	A	3.2V	LED Power (+)
18	K	0V	LED Power (-)

ABSOLUTE MAXIMUM RATINGS

ITEM	SYMBOL	MIN.	TYP.	MAX.	UNIT
Supply Voltage For Logic	VDD-VSS	0	-	5.0	V
Supply Voltage For LCD Drive	VDD-Vo	0	-	18.0	V
Input Voltage	Vi	Vss	-	VDD	V

ELECTRICAL CHARACTERISTICS

ITEM	SYMBOL	CONDITION	MIN.	TYP.	MAX.	UNIT	
Supply Voltage For Logic	VDD-VSS	-	2.7	3.0	3.3	V	
LCD Supply Voltage	VDD-Vo	VDD=3.0V Ta=25	9.6	10.2	11.2	V	
Supply Current	IDD	VDD=3.0V	-	2.4	3.5	mA	
Input Voltage	"HIGH" Level	V _{IH}	-	2.2	-	VDD	V
	"LOW" Level	V _{IL}	-	-	-	0.6	V
Output Voltage	"HIGH" Level	V _{OH}	-	2.4	-	-	V
	"LOW" Level	V _{OL}	-	-	-	0.4	V

EXTERNAL DIMENSIONS

