



# BRIGHTTEK

BRIGHTTEK (EUROPE) LIMITED

*Brighten up The World With LED!*



ISO/TS 16949:2009



BS EN ISO 14001:2004



QC 080000 IECQ HSPM

## PRODUCT DATASHEET



- ▶ DC Input Photo Coupler
- ▶ SMD6 Low Profile
- ▶ Zero-Cross TRIAC

### TD306X(SL)(T1)-GV



Release Date: 10 June 2025 Version: A00



## TD306X(SL) Series

### DESCRIPTION:

The TD306X(SL) series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon zero-cross photo TRIAC in a plastic DIP6 package with SMD6 Low Profile lead forming option.



### FEATURES:

- High isolation 5000Vrms
- DC input with zero-cross photo TRIAC output
- Operating temperature range -40°C to +100°C
- REACH & RoHS compliance
- MSL class 1
- Regulatory Approvals:
  - UL - UL1577
  - VDE - EN60747-5-5 (VDE0884-5)
  - CQC - GB4943.1, GB8898
- Packing: 1000pcs/reel

### APPLICATIONS:

- Solenoid/valve controls
- Lighting controls
- Motor controls
- Temperature controls
- Static AC power switches
- Solid state relays
- Interfacing microprocessors to 115 to 240VAC peripherals



Partner with:  LIGHTNING



## NAMING & ORDERING INFORMATION:

### Naming Information:

|                               |  |
|-------------------------------|--|
| <b>TD306 X (SL) (T1)- G V</b> |  |
| <b>TD306</b>                  | Part Number                                      |
| <b>X</b>                      | Selection: LED Trigger Current (X=1~3)           |
| <b>SL</b>                     | Lead Form Option: SMD6 Low Profile               |
| <b>T1</b>                     | Selection: Tape and Reel Option (T1(default)/T2) |
| <b>G</b>                      | Green Option                                     |
| <b>V</b>                      | VDE Option                                       |

### Ordering Information:

| <b>TD306X(SL)(T1)-GV</b>                   |                 |        |      |      |      |  |
|--|-----------------|--------|------|------|------|--|
| X = Selection: LED Trigger Current (X=1~3) |                 |        |      |      |      |  |
| Part Number                                | Symbol          | Values |      |      | Unit | Test Condition                                   |
|  |                 | Min.   | Typ. | Max. |      |  |
| TD3061(SL)(T1)-GV                          | I <sub>FT</sub> | ---    | ---  | 15   | mA   | I <sub>TM</sub> =100mA<br>Terminal<br>Voltage=3V |
| TD3062(SL)(T1)-GV                          |                 | ---    | ---  | 10   |      |  |
| TD3063(SL)(T1)-GV                          |                 | ---    | ---  | 5    |      |  |

| Version No. | Original Release Date |
|-------------|-----------------------|
| Rev: A00    | 05/09/2024            |

## SCHEMATIC DIAGRAM & MARKING:

Schematic Diagram:

| PIN Definition |           |
|----------------|-----------|
| 1              | Anode     |
| 2              | Cathode   |
| 3              | NC        |
| 4              | Terminal  |
| 5              | Substrate |
| 6              | Terminal  |

Marking Information:

| Marking Definition |                    |
|--------------------|--------------------|
| TD                 | Manufacturer Code  |
| 306X               | Part Number & Rank |
| V                  | VDE Applicable     |
| Y                  | Fiscal Year        |
| A                  | Manufacturing Code |
| WW                 | Work Week          |

Labelling Information:

|   |  |
|---|--|
|  <b>BRIGHTTEK</b><br>BRIGHTTEK (EUROPE) LIMITED  LIGHTNING<br>Part No.: XXXXXXXXXXXX      Bin Code: X<br><br>Lot No.: XXXXXXXX<br>Date Code: XXXX<br>QTY: XXX PCS<br><br>MSL: 1<br>     <br>Made in Quanzhou Fujian | This product is manufactured, tested, and packed by  |
|   | <br>for more details, please visit <a href="http://www.tdled.com">www.tdled.com</a> |

## ABSOLUTE CHARACTERISTICS:

### Absolute Maximum Ratings:

| Parameter   | Symbol       | Ratings  | Unit |
|---|--------------|----------|------|
| INPUT   |              |          |      |
| Forward Current                                   | $I_F$        | 60       | mA   |
| Reverse Voltage                                   | $V_R$        | 6        | V    |
| Junction Temperature                              | $T_j$        | 125      | °C   |
| Input Power Dissipation                           | $P_i$        | 100      | mW   |
| OUTPUT  |              |          |      |
| Off-State Output Terminal Voltage                 | $V_{DRM}$    | 600      | V    |
| Peak Repetitive Surge Current<br>PW=100μs, 120pps | $I_{TSM}$    | 1        | A    |
| On-State RMS Current                              | $I_{T(RMS)}$ | 100      | mA   |
| Junction Temperature                              | $T_j$        | 125      | °C   |
| Output Power Dissipation                          | $P_o$        | 300      | mW   |
| COMMON  |              |          |      |
| Total Power Dissipation                           | $P_{tot}$    | 400      | mW   |
| Isolation Voltage                                 | $V_{iso}$    | 5000 *1  | Vrms |
| Operating Temperature                             | $T_{opr}$    | -40~+100 | °C   |
| Storage Temperature                               | $T_{stg}$    | -55~+125 | °C   |
| Soldering Temperature                             | $T_{sol}$    | 260 *2   | °C   |

\*1. AC for 1 minute, R.H.=40~60%.

\*2. For 10 seconds max.

## ELECTRICAL CHARACTERISTICS:


Electrical Optical Characteristics at  $T_a=25^{\circ}\text{C}$ :

| Parameter                                     |        | Symbol            | Values |       |        | Unit | Test Condition  |
|---|--------|-------------------|--------|-------|--------|------|---|
|   |        |                   | Min.   | Typ.  | Max.   |      |   |
| INPUT   |        |                   |        |       |        |      |   |
| Forward Voltage                               |        | V <sub>F</sub>    | ---    | 1.24  | 1.4    | V    | I <sub>F</sub> =10mA  |
| Reverse Current                               |        | I <sub>R</sub>    | ---    | ---   | 10     | μA   | V <sub>R</sub> =6V  |
| Input Capacitance                             |        | C <sub>IN</sub>   | ---    | 8.5   | 250    | pF   | V=0, f=1kHz   |
| OUTPUT  |        |                   |        |       |        |      |   |
| Peak Off-State Current<br>Either Direction    |        | I <sub>DRM</sub>  | ---    | ---   | 500 *1 | nA   | V <sub>DRM</sub> =Rated V <sub>DRM</sub><br>I <sub>F</sub> =0                     |
| Peak Off-State Voltage<br>Either Direction    |        | V <sub>TM</sub>   | ---    | 1.59  | 2.5    | V    | I <sub>TM</sub> =100mA  |
| Critical Rate of Rise of Off-State<br>Voltage |        | dV/dt             | 1000   | ---   | ---    | V/μs | V <sub>PEAK</sub> =400V<br>I <sub>F</sub> =0                                      |
| TRANSFER CHARACTERISTICS                      |        |                   |        |       |        |      |   |
| LED Trigger Current                           | TD3061 | I <sub>FT</sub>   | ---    | ---   | 15     | mA   | I <sub>TM</sub> =100mA<br>Terminal<br>Voltage=3V                                  |
|   | TD3062 |                   | ---    | ---   | 10     |      |   |
|   | TD3063 |                   | ---    | ---   | 5      |      |   |
| Holding Current                               |        | I <sub>H</sub>    | ---    | 237   | ---    | μA   | ---   |
| Isolation Resistance                          |        | R <sub>ISO</sub>  | 10^12  | 10^14 | ---    | Ω    | DC=500V,<br>40~60% R.H.   |
| Floating Capacitance                          |        | C <sub>IO</sub>   | ---    | 0.4   | ---    | pF   | V=0, f=1MHz   |
| ZERO-CROSSING CHARACTERISTICS                 |        |                   |        |       |        |      |   |
| Inhibit Voltage                               |        | V <sub>INH</sub>  | ---    | ---   | 20     | V    | I <sub>F</sub> =Rated I <sub>FT</sub>   |
| Leakage in Inhibited State                    |        | I <sub>DRM2</sub> | ---    | ---   | 500    | μA   | I <sub>F</sub> =Rated I <sub>FT</sub><br>V <sub>DRM</sub> =Rated V <sub>DRM</sub> |


\*1. Test voltage must be applied within  $dV/dt$  rating.

## CHARACTERISTIC CURVES:


Forward Current v.s. Ambient Temperature




On-State Terminal Current v.s. Ambient Temp.




Forward Current v.s. Forward Voltage




Off-State Terminal Current v.s. Ambient Temperature



Normalized Off-State Terminal Voltage v.s. Ambient Temperature




Normalized Trigger Current v.s. LED Trigger Pulse Width




## CHARACTERISTIC CURVES:


Normalized Trigger Current v.s. Ambient Temperature




On-State Terminal Voltage v.s. Ambient Temperature




On-State Terminal Voltage v.s. On-State Terminal Current




Holding Current v.s. Ambient Temperature



Normalized Inhibit Voltage v.s. Ambient Temperature




Normalized Leakage in Inhibit State v.s. Ambient Temperature




## CHARACTERISTIC CURVES:

Turn On Time v.s. Forward Current




Turn On Time v.s. Ambient Temperature






## TEST CIRCUIT:

### Test Circuit and Waveforms of Turn On Time:




### Test Circuit and Waveforms of $dv/dt$ :



## OUTLINE DIMENSION:


### Package Dimension:

#### Surface Mount Low Profile Lead Forming - SMD (SL Type)



1. All dimensions are in millimetre (mm).


### Recommended Soldering Mask:



1. Dimensions are in millimetre (mm).

## PACKING SPECIFICATION:

Reel Dimension:




## PACKING SPECIFICATION:

Box Dimension:


T1/T2: 3 reels (3Kpcs)/inner box, 5 inner boxes (15Kpcs)/carton



● L x W x H = 36cm x 36cm x 6.9cm




● L x W x H = 45cm x 38cm x 38cm





## RECOMMENDED SOLDERING PROFILE:


Reflow Information:



| Profile Feature                                  | Sn-Pb Assembly Profile | Pb-Free Assembly Profile |
|--|------------------------|--------------------------|
| Temperature Min. ( $T_{smin}$ )                  | 100°C                  | 150°C                    |
| Temperature Max. ( $T_{smax}$ )                  | 150°C                  | 200°C                    |
| Time ( $t_s$ ) from ( $T_{smin}$ to $T_{smax}$ ) | 60-120 seconds         | 60-120 seconds           |
| Ramp-up Rate ( $T_L$ to $T_P$ )                  | 3°C/second max.        | 3°C/second max.          |
| Liquidous Temperature ( $T_L$ )                  | 183°C                  | 217°C                    |
| Time ( $t_L$ ) Maintained Above ( $T_L$ )        | 60-150 seconds         | 60-150 seconds           |
| Peak Body Package Temperature                    | 235°C +0°C / -5°C      | 260°C +0°C / -5°C        |
| Time ( $t_P$ ) within 5°C of 260°C               | 20 seconds             | 30 seconds               |
| Ramp-down Rate ( $T_P$ to $T_L$ )                | 6°C/second max.        | 6°C/second max.          |
| Time 25°C to Peak Temperature                    | 6 minutes max.         | 8 minutes max.           |

## RECOMMENDED SOLDERING PROFILE:

Wave Soldering (JESD22-A111 Compliant):



Hand Soldering:

|                       |            |
|-----------------------|------------|
| Soldering Temperature | 380±5°C    |
| Soldering Time        | 3 sec max. |

Note:

- One time soldering is recommended for all soldering methods.
- Do not solder more than three times for IR reflow soldering.