


# N0D19S26

◆Outline(L\*W\*H): 1.6\*1.5\*0.6mm

◆Good thermal dissipation & optical uniformity



## Table of Contents

Product Code Method -----	2
Maximum Rating-----	2
Typical Product Characteristics-----	3
Range of Bins-----	4
Color Coordinate Comparison-----	5
Electronic-optical Characteristics-----	6
Dimensions-----	8
Reflow Profile-----	9
Test Circuit and Handling Precautions-----	10
Packing-----	11
Precautions-----	13
Test Items and Results of Reliability-----	14

## Features

- Forward current:  $\leq 30\text{mA}$
- Typical view angle 50% Iv:  $140^\circ$
- RoHS and REACH-compliant
- Lens color: yellowish
- Qualified according to JEDEC moisturevity Level 3
- ESD level 1kV(HBM)

## Applications

- Indoor signage display applications
- Indoor decorating and entertainment design
- Flat backlight for LCD. Switch and symbol
- Indicator and backlighting for all consumer electronics

**■ Product Code Method**

①	②	③	④	⑤
Process Type	Category	LED Type	Lead Frame Size	Dice wavelength & luminous rank
1: normal process	S: SMD LED	A: PCB top view B: PCB side view	0606: 1.6*1.5mm	A2: amber W3:white

⑥	⑦	⑧	⑨
Lap Polarity	Cap Color	PCB Module Code	Flow Code
0: non-common anode and non-common cathode	C: yellowish	B: article mode	01: no expression above meaning for company

**■ Maximum Rating(Ta=25°C)**

Characteristics	Symbol	Typical	Unit
DC forward current	I <sub>F</sub>	30	mA
Pulse forward current <sup>*3</sup>	I <sub>PF</sub>	100	mA
Reverse current	V <sub>R</sub>	5	V
Junction temperature	T <sub>J</sub>	110	°C
Operating temperature range	T <sub>OP</sub>	-40-80	°C
Storage temperature range	T <sub>STG</sub>	-40-100	°C
Soldering temperature <sup>*4</sup>	T <sub>SD</sub>	260	°C

Note 1: There is no maximum or typical voltage parameter

2: For other ambient, limited setting of current will be depended on de-rating curves.

3: Duty 1/10, pulse width 0.1ms

4: The maximum of soldering time is 5 seconds in T<sub>SD</sub>



■ Typical Product Characteristics (Ta=25°C)

Characteristics	Symbol	Amber			White			Unit	Test condition
		Min.	Typ.	Max.	Min.	Typ.	Max.		
Forward Voltage	V <sub>F</sub>	1.6		2.5	2.5	-	3.4	V	I <sub>F</sub> =5mA
Reverse Current	I <sub>R</sub>	-	-	10	-	-	10	μA	V <sub>R</sub> = 5V
Luminous Intensity	I <sub>v</sub>	-	25	-	-	180	-	mcd	I <sub>F</sub> =5mA
View Angle	□2θ <sub>1/2</sub>	-	140	-	-	140	-	deg	I <sub>F</sub> =5mA
Dominant Wavelength (Color Coordinate)	λ <sub>d</sub> (x)	600	-	612	-	0.31		nm	I <sub>F</sub> =5mA
	y	-	-	-	-	0.32	-		

Notes: 1. Measurement Errors:

Forward Voltage: ±0.1V, Luminous Intensity: ±10% I<sub>v</sub>, Viewing Angle (2θ<sub>1/2</sub>): ±5%, Dominant Wavelength ±1.0nm

Color Coordinate (x, y) ±0.006

2. Electrical-Optical characteristics (Ta=25°C)



■ **Range of Bins**

**1). Forward Voltage Bins ( $I_F=5mA$ )**

Amber			White		
Bin Code	Min. $V_F$ (v)	Max. $V_F$ (v)	Bin Code	Min. $V_F$ (v)	Max. $V_F$ (v)
b	1.6	1.9	e	2.5	2.8
c	1.9	2.2	f	2.8	3.1
d	2.2	2.5	g	3.1	3.4

**2). Luminous Intensity Bins ( $I_F=5mA$ )**

Amber			White		
Bin Code	Min. $I_V$ (mcd)	Max. $I_V$ (mcd)	Bin Code	Min. $I_V$ (mcd)	Max. $I_V$ (mcd)
B	16	20	K	125	160
C	20	25	L	160	200
D	25	32	M	200	250
E	32	40	N	250	320


■ **Range of Bins**

**3). Dominant Wavelength Bins ( $I_F=5mA$ )**

Amber		
Bin Code	Min. $\lambda_d$ (nm)	Max. $\lambda_d$ (nm)
A	600	603
B	603	606
C	606	609
D	609	612



■ **Color Coordinate Comparison**




**Color Rank**


A1	X	0.29	0.29	0.31	0.31	0.29
	Y	0.339	0.307	0.335	0.367	0.339
A2	X	0.31	0.31	0.33	0.33	0.31
	Y	0.367	0.335	0.363	0.395	0.367
A3	X	0.33	0.33	0.35	0.35	0.33
	Y	0.395	0.363	0.391	0.423	0.395
A4	X	0.29	0.29	0.31	0.31	0.29
	Y	0.307	0.275	0.303	0.335	0.307
A5	X	0.31	0.31	0.33	0.33	0.31
	Y	0.335	0.303	0.331	0.363	0.335
A6	X	0.33	0.33	0.35	0.35	0.33
	Y	0.363	0.331	0.359	0.391	0.363

■ Optical Characteristics - Amber


1).Relative Spectral Distribution




2).Typical Spatial Distribution




3).Relative Luminous Flux .Current




4).Relative Luminous Flux .Ambient Temperature




5).Electrical Characteristics




6).Forward Voltage Temperature



7).Wavelength and current




8).Thermal Design




■ Optical Characteristics -White


1).Relative Spectral Distribution




2).Typical Spatial Distribution




3). Relative Luminous Flux .Current




4). Relative Luminous Flux .Ambient Temperature




5).Electrical Characteristics




6).Forward Voltage Temperature




7). Relative Emission Efficiency and current




8). Thermal Design



■ **Dimensions**



**Recommend Padlayout**




- Notes:
1. All dimensions are in millimeters (inch)
  2. Tolerance is  $\pm 0.1$  (0.004) mm unless otherwise noted
  3. Specifications are subject to change without notice.






■ **Reflow Profile**

**1. IR reflow soldering Profile for Lead Free solder**



**2. IR reflow soldering Profile for Lead solder**



**Notes:**


1. We recommend the reflow temperature 240°C ( $\pm 5^\circ\text{C}$ ).the maximum soldering temperature should be limited to 260°C.
2. Don't cause stress to the silicone resin while it is exposed to high temperature.
3. Number of reflow process shall be less than 3 times.



■ **Test Circuit and Handling Precautions**

---

**1. Test circuit**



**2. Handling precautions**

**2.1. Over-current-proof**

Customer must apply resistors for protection; otherwise slight voltage shift will cause big current change (Burn out will happen).

**2.2. Storage**

1). It is recommended to store the products in the following conditions:

Humidity: 60% R.H. Max.

Temperature : 5°C~30°C (41°F~86°F)

2). Shelf life in sealed bag: 12 month at <5°C~30°C and <60% R.H. after the package is Opened, the products should be used within a week or they should be keeping to stored at  $\leq 20\%$ R.H. with zip-lock sealed.

**2.3. Baking**

It is recommended to baking before soldering when the pack is unsealed after 24hrs.

The Conditions are as followings:


1). 60±3°C X 6hrs and <5%RH, for reel

2). 125±3°C X 2hrs, for single LED


It shall be normal to see slight color fading of carrier (light yellow) after baking in process

■ Packing


● Feeding Direction




● Dimensions of Reel (Unit: mm)



● Dimensions of Tape (Unit: mm)



● Arrangement of Tape




Notes:

1. Empty component pockets are sealed with top cover tape;
2. The max loss number of SMD is 2pcs;
3. The cathode is oriented towards the tape sprocket hole in accordance with ANSI/EIA RS-481 specifications;
4. 4000pcs per reel

■ **Packing**

---

● **Packaging specifications**



**Notes:**

Reeled product (max.4,000) is packed in a sealed moisture-proof bag. Seven bags are packed in an inner box (size: about 260 X 230 X 100 mm) and four inner boxes are in an outer box (size: about 480 X 275 X 215 mm). On the label of moisture-proof bag, there should be the information of Part No., Lot No. and quantity number; also the total quantity number should be on inspection request form on outer box.

■ **Precautions**

---


**1. Abnormal situation caused by improper setting of collet**

To choose the right collet is the key issue in improving the product's quality. LED is different from other electronic components, which is not only about electrical output but also for optical output. This characteristic made LED more fragile in the process of SMT. If the collet's lowering down height is not well set, it will bring damage to the gold wire at the time of collet's picking up and loading which will cause the LED fail to light up, light up now and then or other quality problems


**2. How to choose the collet**

During SMT, please choose the collet that has larger outer diameter than the lighting area of lens, in case that improper position of collet will damage the gold wire inside the LED. Different collets fit for different products, please refer to the following pictures cross out

**Outer diameter of collet should be larger than the lighting area**



**Picture 1(√)**



**Picture 2(X)**

**3. Other points for attention**

- A. No pressure should be exerted to the epoxy shell of the SMD under high temperature.
- B. Do not scratch or wipe the lens since the lens and gold wire inside are rather fragile and cross out easy to break.
- C. LED should be used as soon as possible when being taken out of the original package, and should be stored in anti-moisture and anti-ESD package.

**4. This usage and handling instruction is only for your reference.**



■ **Test Items and Results of Reliability**

Test Item	Test Conditions	Duration/ Cycle	Number of Damage	Reference
Temperature Cycle	-40°C 30min ↑↓1min 100°C 30min	100 cycles	0/22	JEITA ED-4701 300 303
High Temperature Storage	T <sub>a</sub> =100 ±5°C	1000 hrs	0/22	EIAJED-4701 200 201
High Humidity Heat Life Test	T <sub>a</sub> =85°C RH=85% I <sub>F</sub> =10mA	500 hrs	0/22	Tested with Brighttek standard
Humidity Heat Storage	T <sub>a</sub> =85°C RH=85%	1000 hrs	0/22	EIAJED-4701 100 103
Life Test	T <sub>a</sub> =25°C I <sub>F</sub> =20mA	1000 hrs	0/22	Tested with Brighttek standard
Low Temperature Life Test	T <sub>a</sub> =-40°C I <sub>F</sub> =20mA	1000 hrs	0/22	Tested with Brighttek standard
High Temperature Life Test	T <sub>a</sub> =85°C I <sub>F</sub> =20mA	1000 hrs	0/22	Tested with Brighttek standard

<b>*Criteria for Judging</b>				
Item	Symbol	Condition	Criteria for Judgment of Pass	
			Min	Max
Forward Voltage	V <sub>F</sub>	I <sub>F</sub> =5mA	-	USL* <sup>1</sup> ×1.1
Reverse Current	I <sub>R</sub>	V <sub>R</sub> = 5V	-	10μA
Luminous Intensity	I <sub>v</sub>	I <sub>F</sub> =5mA	LSL* <sup>2</sup> ×0.7	-

[Note] USL\*<sup>1</sup>: Upper Specification Level

LSL\*<sup>2</sup>: Lower Specification Level