



BRIGHTTEK
BRIGHTTEK (EUROPE) LIMITED

Brighten Up The World With LED!



ISO/TS 16949:2009



BS EN ISO 14001:2004



QC 080000 IECQ HSPM

PRODUCT DATASHEET




- ▶ PCB Side View
- ▶ 1204SV (3010) 2.0t
- ▶ Infrared (IR) 945nm

NOF41S46SV



Release Date: 29 November 2022 Version: A1.1



1204SV (3010) 2.0t

RoHS
Compliant



FEATURES:

- **Package:** Side View PCB / CHIP LED
- **Forward Current:** 20mA
- **Forward Voltage (typ.):** 1.3V
- **Radiant Intensity (typ.):** 0.73mW/sr@20mA
- **Colour:** Infrared (IR)
- **Peak Wavelength:** 945nm
- **Viewing angle:** 150°
- **Materials:**
 - Die: GaAlAs/GaAs
 - Resin: Epoxy (Water Clear)
 - L/F Finish: Au
- **Operating Temperature:** -40~+85°C
- **Storage Temperature:** -40~+85°C
- **Grouping parameters:**
 - Forward voltage
 - Radiant intensity
 - Peak wavelength
- **Soldering methods:** Reflow
- **MSL Level:** 3 acc. to JEDEC
- **Packing:** 8mm tape with max.3000/reel, ø180mm (7")

APPLICATIONS:

- Sensor
- Security Device
- Detector

CHARACTERISTICS:

Absolute Maximum Characteristics (Ta=25°C)

Parameter	Symbol	Ratings	Unit
Forward Current	I _F	50	mA
Peak Forward Current (Pulse Width 100μs, Duty Cycle 1%)	I _{FP}	1	A
Reverse Voltage	V _R	5	V
Reverse Current @5V	I _R	10	μA
Power Dissipation	P _D	80	mW
Operating Temperature	T _{OPR}	-40~+85	°C
Storage Temperature	T _{STG}	-40~+85	°C


Electrical & Optical Characteristics (Ta=25°C)

Parameter	Symbol	Values			Unit	Test Condition
		Min.	Typ.	Max.		
Forward Voltage	V _F	0.8	1.3	1.6	V	I _F =20mA
Radiant Intensity	I _e	0.6	0.73	1.6	mW/sr	I _F =20mA
Peak Wavelength	λ _P	930	945	950	nm	I _F =20mA
Spectral Line Half Bandwidth	Δλ	---	27	---	nm	I _F =20mA
Viewing Angle	2θ _{1/2}	---	150	---	deg	I _F =20mA

- Luminous intensity (I_v) ±15%, Forward Voltage (V_F) ±0.1V, Viewing angle(2θ_{1/2}) ±5%


OUTLINE DIMENSION:

Package Dimension:



1. All dimensions are in millimetre (mm).
2. Tolerance $\pm 0.2\text{mm}$, unless otherwise noted.

Recommended Soldering Pad Dimension:



1. Dimensions are in millimetre (mm).
2. Tolerance $\pm 0.1\text{mm}$ with angle tolerance $\pm 0.5^\circ$.

BINNING GROUPS:

 Forward Voltage Classifications ($I_F = 20\text{mA}$):

Code	Min.	Max.	Unit
□	0.8	1.6	V

 Radiant Intensity Classifications ($I_F = 20\text{mA}$):

Code	Min.	Max.	Unit
B	0.60	1.10	mW/sr
C	1.10	1.60	

 Peak Wavelength Classifications ($I_F = 20\text{mA}$):


Code	Min.	Max.	Unit
□	930	950	nm

Example Group Name on Label:


- B□ 20 = □ (0.8~1.6V) ▶ B (0.6~1.1mW/sr) ▶ □ (930~950nm) ▶ 20 ($I_F=20\text{mA}$)

ELECTRO-OPTICAL CHARACTERISTICS:


Relative Spectral Distribution



Forward Current v.s. Forward Voltage




Directive Radiation



RECOMMENDED SOLDERING PROFILE:

Reflow Solder:




Note:

1. Recommend reflow temperature 245°C. The maximum soldering temperature should be limited to 260°C.
2. Maximum reflow soldering: 2 times.
3. Before, during, and after soldering, should not apply stress on the components and PCB board.

PACKING SPECIFICATION:

Reel Dimension:



PRECAUTIONS OF USE:

Storage:

It is recommended to store the products in the following conditions:

- Humidity: 60% R.H. Max.
- Temperature: 5°C~30°C (41°F ~86°F).

Shelf life in sealed bag: 12 months at 5°C~30°C and <60% R.H.

Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a damp-proof box with desiccating agent <10% R.H. and apply baking before use.

Baking:

It is recommended to bake the LED before soldering if the pack has been unsealed for longer than 24hrs.

The suggested baking conditions are as followings:

- 60±3°C x 36hrs and <5%RH, taped / reel package.

It's normal to see slight color fading of carrier (light yellow) after baking in process.

Testing Circuit:



Must apply resistor(s) for protection (over current proof).

Cleaning:

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED carrier / package. Avoid putting any stress force directly on to the LED lens.

ESD (Electrostatic Discharge):

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handling the LED all time. All devices, equipment, machinery, work tables, and storage racks must be properly grounded.

In the events of manual working in process, make sure the devices are well protected from ESD at any time.

REVISION RECORD:

Version	Date	Summary of Revision
A1.0	11/09/2017	Datasheet set-up.
A1.1	29/11/2022	Revise bin code.