



BRIGHTTEK
BRIGHTTEK (EUROPE) LIMITED

Brighten Up The World With LED!



ISO/TS 16949:2009



BS EN ISO 14001:2004



QC 080000 IECQ HSPM

PRODUCT DATASHEET




- ▶ PTH/THT Digit Display
- ▶ 2.3" Single Digit 8.
- ▶ Red/Green/Blue

NOM58D25BS



Release Date: 08 December 2023 Version: A1.1



THT Digit Display

THT Digit Display

RoHS
Compliant



FEATURES:

- **Package:** PTH/THT 2.3" Single Digit Black Surface Full Colour Display / 7-Segment
- **Forward Current:** 20/20/20mA*
- **Forward Voltage (typ.):** 2.0/3.1/3.1V
- **Luminous Intensity (typ.):** 20/25/18mcd@20mA
- **Colour:** Red/Green/Blue
- **Dominant Wavelength (typ.):** 625/525/467nm
- **Materials:**
 - Die: AlInGaP/InGaN/InGaN
 - Resin: Epoxy (White Diffused)
- **Operating Temperature:** -40~+85°C
- **Storage Temperature:** -40~+100°C
- **Grouping Parameters:**
 - Forward voltage
 - Luminous intensity
 - Dominant wavelength
- **Soldering Methods:** Hand; Soldering Heat (DIP)
- **Packing:** bulk in carton

* in the order of Red/Green/Blue

APPLICATIONS:

- Indicator
- Signal
- 3C Application
- Counter
- White Goods
- Audio Device

CHARACTERISTICS:

Absolute Maximum Characteristics (Ta=25°C)

| Parameter | Symbol | Ratings | Unit |
|-------------------------------------|------------------|-----------|------|
| Forward Current | I _F | 25/30/30* | mA |
| Peak Forward Current Duty 1/10@1KHz | I _{FP} | 100 | mA |
| Reverse Current @5V | I _R | 10 | μA |
| Reverse Voltage | V _R | 5 | V |
| Power Dissipation | PD | 85 | mW |
| Electrostatic Discharge | ESD | 200 | V |
| Operating Temperature | T _{OPR} | -40~+85 | °C |
| Storage Temperature | T _{STG} | -40~+100 | °C |

* in the order of Red/Green/Blue


Electrical & Optical Characteristics (Ta=25°C)

| Parameter | Symbol | Values | | | Unit | Test Condition |
|------------------------------|----------------|--------------|-------------|-------------|------|----------------------|
| | | Min. | Typ. | Max. | | |
| Forward Voltage | V _F | 1.8/2.8/2.8* | 2.0/3.1/3.1 | 2.4/3.5/3.5 | V | I _F =20mA |
| Luminous Intensity | I _V | 15/20/14** | 20/25/18 | 25/30/22 | mcd | I _F =20mA |
| Dominant Wavelength | λ _D | 620/517/464 | 625/525/467 | 630/530/472 | nm | I _F =20mA |
| Peak Wavelength | λ _P | --- | 635/525/470 | --- | nm | I _F =20mA |
| Spectral Line Half Bandwidth | Δλ | --- | 45/36/40 | --- | nm | I _F =20mA |

1. Luminous intensity (I_V) ±15%, Forward Voltage (V_F) ±0.1V, Viewing angle(2θ_{1/2}) ±5%
2. * in the order of Red/Green/Blue
3. ** value per segment

OUTLINE DIMENSION:


Package Dimension:




1. All dimensions are in millimetre (mm).
2. Tolerance ± 0.2 mm, unless otherwise noted.

ELECTRO-OPTICAL CHARACTERISTICS (RED):


Relative Intensity v.s. Forward Current




Forward Current v.s. Forward Voltage



Relative Intensity v.s. Temperature




Forward Current v.s. Temperature




ELECTRO-OPTICAL CHARACTERISTICS (GREEN):


Relative Intensity v.s. Forward Current




Forward Current v.s. Forward Voltage



Relative Intensity v.s. Temperature




Forward Current v.s. Temperature




ELECTRO-OPTICAL CHARACTERISTICS (BLUE):


Relative Intensity v.s. Forward Current




Forward Current v.s. Forward Voltage



Relative Intensity v.s. Temperature



Forward Current v.s. Temperature




RECOMMENDED SOLDERING PROFILE:

Hand Solder (Solder Iron):

- Temperature at tip of iron: 350°C Max.
- Soldering Time: 3 seconds \pm 1 sec.

Soldering Heat (DIP):



Note:

1. Maximum reflow soldering: 1 time.
2. Before, during, and after soldering, should not apply stress on the components and PCB board.

PRECAUTIONS OF USE:

Storage:

It is recommended to store the products in the following conditions:

- Humidity: 60% R.H. Max.
- Temperature: 5°C~30°C (41°F ~86°F).

Shelf life in sealed bag: 12 months at 5°C~30°C and <60% R.H.

Once the package is opened, the products should be used within a year. Otherwise, they should be kept in a damp-proof box with desiccating agent <10% R.H. and apply baking before use.


Baking:

It is recommended to bake the LED before soldering if the pack has been unsealed for longer than 24hrs. The suggested baking conditions are as followings:

- 60±5°C x 24hrs and <5%RH, taped / reel package.

It's normal to see slight color fading of carrier (light yellow) after baking in process.

Testing Circuit:



Must apply resistor(s) for protection (over current proof).

Cleaning:

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED carrier / package. Avoid putting any stress force directly on to the LED lens.

ESD (Electrostatic Discharge):

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handling the LED all time. All devices, equipment, machinery, work tables, and storage racks must be properly grounded.

In the events of manual working in process, make sure the devices are well protected from ESD at any time.

REVISION RECORD:

| Version | Date | Summary of Revision |
|---------|------------|---------------------------|
| A1.0 | 06/04/2023 | Datasheet set-up. |
| A1.1 | 08/12/2023 | Revise storage condition. |