



BRIGHTTEK
BRIGHTTEK (EUROPE) LIMITED

Brighten Up The World With LED!



ISO/TS 16949:2009



BS EN ISO 14001:2004



QC 080000 IECQ HSPM

PRODUCT DATASHEET



- ▶ PLCC Side View LED
- ▶ 3810SV 0.60t
- ▶ Sky White (Ice Blue)

NOW69S19SV



Release Date: 27 June 2026 Version: A1.0



3810SV 0.60t



FEATURES:

- **Package:** PLCC Side View SMD LED
- **Forward Current:** 20mA
- **Forward Voltage (typ.):** 3.2V
- **Luminous Intensity (typ.):** 2685mcd@20mA
- **Colour:** Sky White (Ice Blue)
- **Colour Temperature (typ.):** X=0.2850; Y=0.2650
- **Viewing Angle:** 120°
- **Materials:**
 - Resin: Silicone (Yellow Diffused)
- **Operating Temperature:** -40~+85°C
- **Storage Temperature:** -40~+100°C
- **Grouping Parameters:**
 - Forward voltage
 - Luminous intensity
 - CIE Chromaticity
- **Soldering Methods:** Reflow
- **MSL Level:** acc. to JEDEC Level 2a
- **Packing:** 12mm tape with max.2000/reel, ϕ 178mm (7")

APPLICATIONS:

- Backlighting
- Indication Light
- Switch light
- Dashboard
- Consumer Goods

CHARACTERISTICS:

 Absolute Maximum Characteristics ($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Ratings	Unit
Forward Current	I_F	30	mA
Peak Forward Current Duty Cycle 1/10; 1KHz	I_{FP}	80	mA
Power Dissipation	P_D	102	mW
Reverse Voltage	V_R	5	V
Reverse Current @8V	I_R	10	μA
Operating Temperature	T_{OPR}	-40~+85	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	-40~+100	$^{\circ}\text{C}$


 Electrical & Optical Characteristics ($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Values			Unit	Test Condition
		Min.	Typ.	Max.		
Forward Voltage	V_F	---	3.2	3.4	V	$I_F=20\text{mA}$
Luminous Intensity	I_v	---	2685	---	mcd	$I_F=20\text{mA}$
Chromaticity Coordinates	X	---	0.2850	---	---	$I_F=20\text{mA}$
	Y	---	0.2650	---		
Viewing Angle	$2\theta_{1/2}$	---	120	---	deg	$I_F=20\text{mA}$

- Luminous intensity (I_v) $\pm 10\%$, Forward Voltage (V_F) $\pm 0.1\text{V}$.


OUTLINE DIMENSION:

Package Dimension:



1. All dimensions are in millimetre (mm).
2. Tolerance $\pm 0.2\text{mm}$, unless otherwise noted.

Recommended Soldering Pad Dimension:



1. Dimensions are in millimetre (mm).
2. Tolerance $\pm 0.1\text{mm}$ with angle tolerance $\pm 0.5^\circ$.


BINNING GROUPS:

 Forward Voltage Classifications ($I_F = 20\text{mA}$):

Code	Min.	Max.	Unit
H1	2.8	2.9	V
H2	2.9	3.0	
H3	3.0	3.1	
H4	3.1	3.2	
J1	3.2	3.3	
J2	3.3	3.4	

 Luminous Intensity Classifications ($I_F = 20\text{mA}$):


Code	Min.	Max.	Unit
Z71	2250	2385	mcd
Z72	2385	2530	
Z81	2530	2685	
Z82	2685	2850	
Z91	2850	3020	

CIE CHROMATICITY DIAGRAM:

 Chromaticity Coordinates Classifications ($I_F = 20\text{mA}$):


	1		2		3		4	
	X	Y	X	Y	X	Y	X	Y
FEA	0.2820	0.2700	0.2740	0.2560	0.2800	0.2480	0.2880	0.2620
FHA	0.2900	0.2840	0.2820	0.2700	0.2880	0.2620	0.2960	0.2760

ELECTRO-OPTICAL CHARACTERISTICS:


Relative Intensity vs. Forward Current




Forward Current vs. Forward Voltage




Temperature Derating Chart



Relative Intensity vs. Wavelength




Directive Characteristics



RECOMMENDED SOLDERING PROFILE:

Reflow solder:




Note:

1. Recommend reflow temperature 240°C. The maximum soldering temperature should be limited to 260°C.
2. Maximum reflow soldering: 2 times.
3. Before, during, and after soldering, should not apply stress on the components and PCB board.

PACKING SPECIFICATION:

Reel Dimension:



PRECAUTIONS OF USE:

Storage:

It is recommended to store the products in the following conditions:

- Humidity: 60% R.H. Max.
- Temperature: 5°C~30°C (41°F ~86°F).

Shelf life in sealed bag: 12 months at 5°C~30°C and <60% R.H.

Once the package is opened, the products should be used within 4 weeks. Otherwise, they should be kept in a damp-proof box with desiccating agent <10% R.H. and apply baking before use.


Baking:

It is recommended to bake the LED before soldering if the pack has been unsealed for longer than 4 weeks. The suggested baking conditions are as followings:

- 60±3°C x 12~24hrs and <5%RH, taped / reel package.

It's normal to see slight color fading of carrier (light yellow) after baking in process.

Testing Circuit:



Must apply resistor(s) for protection (over current proof).

Cleaning:

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED carrier / package. Avoid putting any stress force directly on to the LED lens.

ESD (Electrostatic Discharge):

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrosatic glove is recommended when handling the LED all time. All devices, equipment, machinery, work tables, and storage racks must be properly grounded.

In the events of manual working in process, make sure the devices are well protected from ESD at any time.

REVISION RECORD:

Version	Date	Summary of Revision
A1.0	27/06/2026	Datasheet set-up.