



**BRIGHTTEK**  
BRIGHTTEK (EUROPE) LIMITED

*Brighten up The World With LED!*



ISO/TS 16949:2009

BSI EM ISO 14001:2004

QC 800000 IECQ HSP98

## PRODUCT DATASHEET



- ▶ PLCC2 Top View SMD
- ▶ 3020 1.3t
- ▶ Yellow 590nm

# NOY03S28



Release Date: 29 May 2022 Version: A1.1



3020 1.3t Series

## 3020 1.3t Series

**RoHS**  
Compliant



### FEATURES:

- **Package:** PLCC2 Single Colour Top View SMD
- **Forward Current:** 20mA
- **Forward Voltage (typ.):** 2.0V
- **Luminous Intensity (typ.):** 800mcd@20mA
- **Colour:** Yellow
- **Wavelength:** 585~597nm
- **Viewing angle:** 120°
- **Materials:**
  - Die: AlGaInP
  - Resin: Silicone (Water Clear)
  - Finishing: Ag plated
- **Operating Temperature:** -40~+80°C
- **Storage Temperature:** -40~+100°C
- **ESD (HBM):** 2KV
- **Grouping parameters:**
  - Forward voltage
  - Luminous intensity
  - Dominant wavelength
- **Soldering methods:** Reflow
- **MSL:** acc. to JEDEC Level 2a
- **Packing:** 8mm tape with max.3000/reel,  $\phi$ 180mm (7")

### APPLICATIONS:

- Backlighting
- Indication Light
- Switch light
- Dashboard
- Decoration Lighting

## CHARACTERISTICS:

### Absolute Maximum Characteristics (Ta=25°C)

Parameter	Symbol	Ratings	Unit
Forward Current	$I_F$	50	mA
Peak Forward Current Duty 1/10; width 0.1ms	$I_{FP}$	100	mA
Reverse Voltage	$V_R$	8	V
Reverse Current @8V	$I_R$	10	$\mu$ A
Junction Temperature	$T_j$	110	°C
Operating Temperature	$T_{OPR}$	-40~+80	°C
Storage Temperature	$T_{STG}$	-40~+100	°C


### Electrical & Optical Characteristics (Ta=25°C)

Parameter	Symbol	Values			Unit	Test Condition
		Min.	Typ.	Max.		
Forward Voltage	$V_F$	1.7	2.0	2.5	V	$I_F=20mA$
Luminous Intensity	$I_v$	600	800	---	mcd	$I_F=20mA$
Dominant Wavelength	$\lambda_D$	585	---	597	nm	$I_F=20mA$
Viewing Angle	$2\theta_{1/2}$	---	120	---	deg	$I_F=20mA$

- Luminous intensity ( $I_v$ )  $\pm 10\%$ , Forward Voltage ( $V_F$ )  $\pm 0.1V$ .


**OUTLINE DIMENSION:**

Package Dimension:



1. All dimensions are in millimetre (mm).
2. Tolerance  $\pm 0.2$ mm, unless otherwise noted.

Recommended Soldering Pad Dimension:



1. Dimensions are in millimetre (mm).
2. Tolerance  $\pm 0.1$ mm with angle tolerance  $\pm 0.5^\circ$ .

**BINNING GROUPS:**


---

 Forward Voltage Classifications ( $I_F = 20\text{mA}$ ):







Code	Min.	Max.	Unit
A	1.7	1.8	V
B	1.8	1.9	
C	1.9	2.0	
D	2.0	2.1	
E	2.1	2.2	
F	2.2	2.3	
G	2.3	2.4	
H	2.4	2.5	

 Luminous Intensity Classifications ( $I_F = 20\text{mA}$ ):


Code	Min.	Max.	Unit
13	600	780	mcd
14	780	1000	
15	1000	1300	

 Dominant Wavelength Classifications ( $I_F = 20\text{mA}$ ):


Code	Min.	Max.	Unit
C	585	588	nm
D	588	591	
E	591	594	
F	594	597	

**ELECTRO-OPTICAL CHARACTERISTICS:**
**Relative Intensity v.s. Forward Current**

**Forward Current v.s. Forward Voltage**

**Forward Current v.s. Wavelength**

**Relative Forward Voltage v.s. Temperature**

**Temperature Derating Chart**

**Relative Intensity Flux v.s. Ambient Temperature**


Relative Intensity v.s. Wavelength




Relative Intensity v.s. Angular Displacement



## RECOMMENDED SOLDERING PROFILE:

Reflow solder:



Note:

1. Recommend reflow temperature 240°C. The maximum soldering temperature should be limited to 260°C.
2. Maximum reflow soldering: 3 times.
3. Before, during, and after soldering, should not apply stress on the components and PCB board.





## PRECAUTIONS OF USE:

---

### Storage:

It is recommended to store the products in the following conditions:

- Humidity: 60% R.H. Max.
- Temperature: 5°C~30°C (41°F ~86°F).

Shelf life in sealed bag: 12 months at 5°C~30°C and <60% R.H.

Once the package is opened, the products should be used within 4 weeks. Otherwise, they should be kept in a damp-proof box with desiccating agent <10% R.H. and apply baking before use.

### Baking:

It is recommended to bake the LED before soldering if the pack has been unsealed for longer than 24hrs.

The suggested baking conditions are as followings:

- 60±3°C x 6hrs and <5%RH, taped / reel package.

It's normal to see slight color fading of carrier (light yellow) after baking in process.

### Testing Circuit:



Must apply resistor(s) for protection (over current proof).

### Cleaning:

Use alcohol-based cleaning solvents such as isopropyl alcohol to clean the LED carrier / package. Avoid putting any stress force directly on to the LED lens.

### ESD (Electrostatic Discharge):

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handling the LED all time. All devices, equipment, machinery, work tables, and storage racks must be properly grounded.

In the events of manual working in process, make sure the devices are well protected from ESD at any time.

**REVISION RECORD:**

---

Version	Date	Summary of Revision
A1.0	27/07/2016	Datasheet set-up.
A1.1	29/05/2022	New datasheet format.