



BRIGHTTEK

BRIGHTTEK (EUROPE) LIMITED

Brighten up The World With LED!



ISO/TS 16949:2009



BS EN ISO 14001:2004



QC 080000 IECQ HSPM

PRODUCT DATASHEET




- ▶ COB Module
- ▶ 15.85x15.85x1.65mm
- ▶ Natural White 5000K

NOW63M20



Release Date: 17 April 2025 Version: A1.1



1 A 1 A C O B M o d u l e

1A1A COB Module

RoHS
Compliant



FEATURES:

- **Package:** Top View COB Light Engine Module
- **Forward Current:** 330~600mA
- **Forward Voltage (typ.):** 35.4V
- **Luminous Flux (typ.):** 1445lm@330mA
- **Colour:** Natural White
- **Colour Temperature (CCT):** 5000K
- **Viewing Angle:** 120°
- **Materials:**
 - Die: InGaN
 - Resin: Silicon (Yellow Diffused)
 - Package: MCPCB
- **Operating Temperature:** -40~+100°C
- **Storage Temperature:** -40~+120°C
- **Grouping Parameters:**
 - Forward Voltage
 - Luminous Flux
 - CIE Chromaticity
- **MSL Level:** 3 according to J-STD020
- **Packing:** 54pcs/tray; 270pcs/carton

APPLICATIONS:

- Commercial Lighting
- Tunnel Light
- Spotlight
- General Lighting

CHARACTERISTICS:

Absolute Maximum Characteristics ($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Ratings	Unit
DC Forward Current	I_F	600	mA
Power Dissipation	P_D	21.72	W
Junction Temperature *	T_j	125	$^{\circ}\text{C}$
Operating Temperature	T_{OPR}	$-40\sim+100$	$^{\circ}\text{C}$
Storage Temperature	T_{STG}	$-40\sim+120$	$^{\circ}\text{C}$
Thermal Resistance	R_{thj-sp}	0.6	$^{\circ}\text{C/W}$
Colour Rendering Index (CRI)	R9	min.83	---
	Ra	min.95	

* R_{thj-sp} is the thermal resistance from LED junction to solder point on MCPCB with electrical power.


Electrical & Optical Characteristics ($T_a=25^{\circ}\text{C}$)

Parameter	Symbol	Values			Unit	Test Condition
		Min.	Typ.	Max.		
Forward Voltage	V_F	33.0	35.4	---	V	$I_F=330\text{mA}$
Luminous Flux	Φ_v	1344	1445	1590	lm	$I_F=330\text{mA}$
Chromaticity Coordinates	X	---	0.3447	---	---	$I_F=330\text{mA}$
	Y	---	0.3553	---		
Colour Temperature	CCT	---	5000	---	K	$I_F=330\text{mA}$
Viewing Angle	$2\theta_{1/2}$	---	120	---	deg	$I_F=330\text{mA}$

1. Luminous flux (Φ_v) $\pm 10\%$, Forward Voltage (V_F) $\pm 0.1\text{V}$, CRI ± 2

OUTLINE DIMENSION:


Package Dimension:




1. All dimensions are in millimetre (mm).
2. Tolerance ± 0.2 mm, unless otherwise noted.



CIE CHROMATICITY DIAGRAM:




Chromaticity Coordinates Classifications ($I_F = 330\text{mA}$):


	Code	Centre		Radius		Angle
		X	Y	a	b	Φ
	50M3 (3 STEP)	0.3447	0.3553	0.008220	0.003540	59.60

ELECTRO-OPTICAL CHARACTERISTICS:


Relative Luminous Flux v.s. Forward Current




Forward Current v.s. Forward Voltage




Relative Luminous Flux v.s. Case Temp.




Forward Voltage v.s. Case Temp.




Relative Spectral Power v.s. Wavelength
(curve shown 2700K/3000K/4000K CCT)



Directive Radiation



Forward Current Derating Curve



PRECAUTIONS OF USE:

Storage:

It is recommended to store the products in the following conditions:

- Humidity: 60% R.H. Max.
- Temperature: 5°C~30°C (41°F ~86°F).

Shelf life in sealed bag: 12 months at 5°C~30°C and <60% R.H.


Once the package is opened, the products should be used within a week. Otherwise, they should be kept in a damp-proof box with desiccating agent <10% R.H. and apply baking before use.

Thermal Management:

Thermal management is a key factor affecting the life of LEDs. The life span of LEDs will reduce with the increase of junction temperature. Please make sure that the temperature of T_j is lower than 125°C during application.

The silicone casting will begin to degrade at 180°C and shall be crack in a few days. Please avoid silicone surface temperature higher than 180°C.

Testing Circuit:



Must apply resistor(s) for protection (over current proof).

Chemical Corrosion:

COB is packaged with soft silicone. Its design is not waterproof, thus please do not dip the COB into water directly. Please avoid silicone contact with sulfur dioxide, sulfuric acid, concentrated hydrochloric acid, and keep dry and sealed during storage.

ESD (Electrostatic Discharge):

Static Electricity or power surge will damage the LED. Use of a conductive wrist band or anti-electrostatic glove is recommended when handling the LED all time. All devices, equipment, machinery, work tables, and storage racks must be properly grounded.

In the events of manual working in process, make sure the devices are well protected from ESD at any time.

REVISION RECORD:

Version	Date	Summary of Revision
A1.0	25/11/2022	Datasheet set-up.
A1.1	17/04/2025	Update specifications.